

Keyword: 1-63A, 1, 1+N, 2, 3, 3+N, 4 Pole, IEC60947-2, SAA, CE, TUV, CB, Nemko, Square indicator window  
SL7-63 MCB

Application

SL7-63 have protective function as shortage as overload, and are used in lighting distribution system in commerce and dwelling, and protect fractional electric motors. And they also have many merits of high protective grade(up to IP20), high breaking capacity, reliable sensitive action, convenient, multi pole assembling, long life ect. They are mainly adapted to the circuit of AC 50Hz, 250V in single pole, 415V in double, three, four poles for protecting overload and short circuit. Mean while, they are also used in turning on or off the electric apparatus and lighting circuit under the normal conditions.



Transparent shell

We supply more comprehensive security: SAFE LOCK, Detailed installation process as follow:



\*Applies to all SL7 products

Specifications

Standard	EN60898(IEC60898);IEC60947-2
Rated current	1-63A
Rated Breaking capacity	6,10kA IEC60898(0.5~63A) 6,10,15kA IEC60947-2(0.5~63A)
Characteristic curve	B,C,D
Max. fuse that can be connected to	100AgL(>10kA)
Selective grade	3
Working ambient temperature	-5°C ~ +40°C
Enclosed protective class	IP20
Electrical life	Not less than 8000 times
Mechanical life	Not less than 20000 times

● Complete accessories

Dimensions / Characteristics curves

